



Univar USA Inc Material Safety Data Sheet

MSDS No:

Version No:

Order No:

Univar USA Inc., 17425 NE Union Hill Rd., Redmond WA 98052
(425) 889 3400

Emergency Assistance

For emergency assistance involving chemicals call
Chemtrec - (800) 424-9300



We create chemistry

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22

Page: 1/9

Version: 2.0

(57134781/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Lutensol® XP 80

Recommended use of the chemical and restriction on use

Recommended use*: surfactant

Suitable for use in industrial sector: chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms: Ethoxylated Alcohol

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Tox.	4 (oral)	Acute toxicity
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Aquatic Acute	3	Hazardous to the aquatic environment - acute

Label elements

Pictogram:

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 2/9
(57134781/SDS_GEN_US/EN)



Signal Word:
Danger

Hazard Statement:
H318 Causes serious eye damage.
H302 Harmful if swallowed.
H402 Harmful to aquatic life.

Precautionary Statements (Prevention):
P280 Wear eye/face protection.
P273 Avoid release to the environment.
P270 Do not eat, drink or smoke when using this product.
P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):
P310 Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301 + P330 IF SWALLOWED: rinse mouth.

Precautionary Statements (Disposal):
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

WARNING:
HARMFUL IF SWALLOWED.
Causes serious eye damage.
Causes skin irritation.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
160875-66-1	100.0 %	Poly(oxy-1,2-ethanediyl), .alpha.-(2-propylheptyl)-.omega.-hydroxy-

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
160875-66-1	100.0 %	Poly(oxy-1,2-ethanediyl), .alpha.-(2-propylheptyl)-.omega.-hydroxy-

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 3/9
(57134781/SDS_GEN_US/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Further important symptoms and effects are so far not known.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Special hazards arising from the substance or mixture

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 4/9
(57134781/SDS_GEN_US/EN)

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures see, section 8.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2), Stainless steel 1.4306 (V2A), Stainless steel 1.4361, Stainless steel 1.4401, Stainless steel 1.4439, Stainless steel 1.4539, Stainless steel 1.4541, Stainless steel 1.4571, Stove-lacquer RDL 50

Further information on storage conditions: Keep container tightly closed and in a cool place.

Storage stability:

Storage temperature: ≤ 70 °C

The packed product is not damaged by low temperatures or by frost. Bulk must be protected from solidification.

Protect from temperatures above: 70 °C

Properties of the product change irreversibly on exceeding the limit temperature.

8. Exposure Controls/Personal Protection

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Breathing protection if breathable aerosols/dust are formed.

Hand protection:

Chemical resistant protective gloves

Consult with glove manufacturer for testing data.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 5/9
(57134781/SDS_GEN_US/EN)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
Odour threshold:		not determined
Colour:	colourless to yellowish	
pH value:	approx. 7	(50 g/l, 20 °C) (DIN EN 1262)
solidification temperature:	approx. 14 °C	(DIN ISO 2207)
Boiling point:		not applicable
Flash point:	approx. 140 °C	(DIN ISO 2592)
Flammability:	not self-igniting	
Lower explosion limit:		For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.
Upper explosion limit:		For liquids not relevant for classification and labelling.
Autoignition:	> 300 °C	
Vapour pressure:	< 0.1 hPa	(20 °C)
Density:	approx. 0.97 g/cm ³	(70 °C) (DIN 51757)
	approx. 1.00 g/cm ³	(25 °C) (DIN 51757)
Relative density:		No data available.
Vapour density:		not determined
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Self-ignition temperature:		not self-igniting
Thermal decomposition:	> 350 °C (DTA)	
Viscosity, dynamic:	approx. 300 mPa.s	(23 °C) (DIN EN 12092)
Particle size:		The substance / product is marketed or used in a non solid or granular form.
Solubility in water:		soluble
Miscibility with water:		miscible in all proportions
Solubility (qualitative):	soluble	
	solvent(s): Ethanol, Ethanol	
Evaporation rate:		not determined
Other Information:		If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 6/9
(57134781/SDS_GEN_US/EN)

Corrosion to metals:
Corrosive effects to metal are not anticipated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

caustics, halogens, Alkalines, acids, reactive chemicals

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
> 350 °C (DTA)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Slightly toxic after single ingestion.

Oral
LD50 judged > 500 mg/kg based on deaths at 200 mg/kg (0/6) and 2000 mg/kg (2/3) plus oral LD50 data on surrogate chemicals.

Irritation / corrosion
Assessment of irritating effects: Causes serious eye damage. Causes skin irritation. May cause irritations to the respiratory tract.

Skin
Species: rabbit
Result: Irritant.
Method: OECD Guideline 404

Eye

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 7/9
(57134781/SDS_GEN_US/EN)

Species: rabbit
Result: Risk of serious damage to eyes.
Method: OECD Guideline 405

Sensitization
Guinea pig maximization test
Species: guinea pig
Result: Skin sensitizing effects were not observed in animal studies.
Method: OECD Guideline 406

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Further important symptoms and effects are so far not known.

12. Ecological Information

Toxicity

Aquatic invertebrates
EC50 (48 h) > 10 - 100 mg/l, Daphnia magna
Analogous: Assessment derived from products with similar chemical character.

Aquatic plants
EC50 (72 h) > 10 - 100 mg/l, Scenedesmus subspicatus
Analogous: Assessment derived from products with similar chemical character.

Chronic toxicity to fish
No observed effect concentration > 1 mg/l
Literature data.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
OECD Guideline 209 aquatic
activated sludge, domestic/EC20 (30 min): approx. > 100 mg/l
Analogous: Assessment derived from products with similar chemical character.
Nominal concentration. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

Persistence and degradability

Elimination information

>= 90 % Bismuth-active substance (mod. OECD 303A)
Analogous: Assessment derived from products with similar chemical character.

> 60 % CO2 formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) Readily biodegradable.

Bioaccumulative potential

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 8/9
(57134781/SDS_GEN_US/EN)

Bioaccumulation potential

Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is possible.

Additional information

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not release untreated into natural waters.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

Safety Data Sheet

Lutensol® XP 80

Revision date : 2014/12/22
Version: 2.0

Page: 9/9
(57134781/SDS_GEN_US/EN)

EPCRA 311/312 (Hazard categories): Acute;

State regulations

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 3 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 3 Flammability: 1 Physical hazard:0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2014/12/22

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Lutensol® XP 80 is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET

Univar USA Inc Material Safety Data Sheet

For Additional Information contact MSDS Coordinator during business hours, Pacific time: (425) 889-3400

Notice

Univar USA Inc. ("Univar") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Univar sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process