

Technical Data Sheet

Toluene

<u>Property</u>	<u>Method</u>	<u>Min</u>	<u>Max</u>	<u>Typical</u>
Density, 60°F	D4052	0.869	0.873	0.8718
Pounds per Gallon	D1250			7.26
Color, Saybolt	D156	28		+30
Color, Pt-Co	D5386		20	5
Copper Corrosion	D849			1A
Sulfur Compounds	D853	Free		Free
Acid Wash Color	D848		2	1-
Acidity	D847	Free		Free
Composition, Wt. %	D2360			
Benzene			<0.06	0.01
Toluene				99.90
Non-Aromatic			1.2	0.05
Distillation, °C	D850			
Total Distillation not to exceed 1° including 110.6°C				
IBP				110.4
10%				110.5
50%				110.6
90%				110.7
DP				110.8

Product meets specification ASTM D841-13 for Nitration Grade Toluene

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.

