

Technical Data Sheet

300-360

<u>Test</u>	<u>UoM</u>	<u>Method</u>	<u>Min</u>	<u>Max</u>	<u>Typical</u>
API Gravity @ 60°F		D4052			55.2
Specific Gravity @ 60/60°F		D4052	0.7540	0.8200	0.7578
Pounds per Gallon @ 60°F	lb/gal	D1250			6.318
Color, Saybolt		D156	28		30
Flash, TCC	°F	D56	100	149	102
Flash, TCC	°C	D56	38	65	39
Distillation, IBP	°F	D86	300		308
Distillation, 50%	°F	D86			328
Distillation, DP	°F	D86		406	362
Aniline Point (°C)	°C	D611	57.2	76.7	71.3
Aniline Point (°F)	°F	D611	134.9	170.0	160.5
Vapor Pressure @ 20°C	mmHg	D2879		7.0000	1.4799
Water Content	ppm	D1533		500	35
Total Aromatics, Wt. %	Wt. %	D5134		1.0	0.00
CU Strip, 2HR @ 100°C		D130		2	1A
BTEX (Detection Limit < 1 ppm)		EPA- SW-846 8260B			ND
Kauri-Butanol Value		D1133	27.0	45.0	29.9
Benzene Content, ppm		D5134		0.5	< 0.5

For the attention you deserve

Extra Notes: Product meets MIL-PRF 680 Type I

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.