

Technical Data Sheet

420-460

Test	UoM	Method	Min	Max	Typical
API Gravity @ 60°F		D4052	43.0	48.0	45.7
Specific Gravity @ 60/60°F		D1250	0.7883	0.8109	0.7983
Pounds per gallon @ 60°F	lb/gal	D1250			6.655
Color, Saybolt		D156	28		30
Viscosity @ 40°C	cSt	D445			1.67
Flash Point, PMCC	°F	D93	200		203
Aniline Point	°F	D611			174.2
Aniline Point	°C	D611			79.0
Distillation, IBP	°F	D86	430		431
Distillation, 5%	°F	D86			438
Distillation, 10%	°F	D86			439
Distillation, 20%	°F	D86			441
Distillation, 30%	°F	D86			442
Distillation, 40%	°F	D86			444
Distillation, 50%	°F	D86			445
Distillation, 60%	°F	D86			448
Distillation, 70%	°F	D86			450
Distillation, 80%	°F	D86			454
Distillation, 90%	°F	D86			460
Distillation, 95%	°F	D86			465
Distillation, DP	°F	D86		480	474
Water Content	ppm	D1533		500	53
Aromatic Content	Wt. %	D5186		1.0	0.00
Benzene Content, ppm		D5134			< 1

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.