

Chemical Distributor
P.O. Box 39524
4578 Brazil Street
Los Angeles, CA 90039
Tel: (323) 245-2345
(818) 242-8486
Fax (818) 242-7804
www.aglayne.com

Technical Data Sheet

Isohexane

| <u>Test</u> | UoM | Method | Min | <u>Max</u> | Typical |
|----------------------------|--------|---------------|-----|---------------------|----------------|
| API Gravity @ 60°F | | D4052 | | | 82.3 |
| Specific Gravity @ 60/60°F | | D1250 | | | 0.6618 |
| Pounds per gallon @ 60°F | lb/gal | D1250 | | | 5.517 |
| Distillation, IBP | °F | D86 | 123 | | 134 |
| Distillation, 5% | °F | D86 | | | 137 |
| Distillation, 10% | °F | D86 | | | 137 |
| Distillation, 20% | °F | D86 | | | 138 |
| Distillation, 30% | °F | D86 | | | 138 |
| Distillation, 40% | °F | D86 | | | 138 |
| Distillation, 50% | °F | D86 | | | 139 |
| Distillation, 60% | °F | D86 | | | 139 |
| Distillation, 70% | °F | D86 | | | 139 |
| Distillation, 80% | °F | D86 | | | 140 |
| Distillation, 90% | °F | D86 | | | 141 |
| Distillation, 95% | °F | D86 | M | Λ Λ | 141 |
| Distillation, DP | °F | D86 | VIF | 150 | 142 |
| Sulfur, ppm | ppm | D5453 | | 5.00 | 0.00 |
| Benzene Content, ppm | ppm | D5134 | | 40.0000 | 0.00 |
| Water Content | ppm | D1533 | | | 10 |
| Isohexane Content | % (V) | D5134 | | | 96.7 |
| n-Hexane | Wt. % | D5134 | | 3.00 | 2.41 |
| CU Strip, 2 HR @ 100°C | | D130 | | 1 | 1A |

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether out product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245–2345.