

Technical Data Sheet

Mineral Spirit

Test	UoM	Method	Min	Max	Typical
API Gravity @ 60°F		D4052	50.0	57.0	53.5
Specific Gravity @ 60/60°F		D1250			0.7648
Pounds per gallon @ 60°F	lb/gal	D1250			6.376
Color, Saybolt		D156	28		30
Flash, TCC	°F	D56	100		116
Flash, TCC	°C	D56	38		46
Distillation, IBP	°F	D86	300		322
Distillation, 5%	°F	D86			334
Distillation, 10%	°F	D86			337
Distillation, 20%	°F	D86			342
Distillation, 30%	°F	D86			347
Distillation, 40%	°F	D86			353
Distillation, 50%	°F	D86			358
Distillation, 60%	°F	D86			366
Distillation, 70%	°F	D86			371
Distillation, 80%	°F	D86			379
Distillation, 90%	°F	D86			391
Distillation, 95%	°F	D86			400
Distillation, DP	°F	D86			360
Water Content	ppm	D1533		500	39
Aromatic Content, Wt. %		D5186		1	0
Refractive Index @ 25°C		D1218			1.4220
Kauri-Butanol Value		D1133			30.2

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.