

Technical Date Sheet

Kerosene

<u>Description</u>	<u>Unit</u>	<u>Method</u>	<u>Min</u>	<u>Max</u>	<u>Results</u>
API Gravity @ 60°F		D4052	46.0		50.6
Pounds per Gallon @ 60°F	lb/gal	D1250			6.478
Color, Saybolt		D156	28		30
Flash, TCC (°F)	°F	D56	142		150
Flash, TCC (°C)	°C	D56			66
Distillation, IBP (°F)	°F	D86	355		372
Water Content	ppm	D1533		500	45
Aromatic Content (Wt.%)	Wt.%	D5186		1.0	0.0
Kauri-Butanol Value		D1133	27.0		30.7
Distillation, DP (°F)	°F	D86		414	411

A.G. LAYNE
CHEMICAL COMPANY

For the attention you deserve

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.